

TBR60-PTSZ1-L-S-SS-SS-2

 "Pass-Thru" Bar Refrigerator, Stainless Steel Ext, 2 Solid Swing Doors Front, 2 Solid Swing Doors Rear



Dimensions		Build		Technical	
External Width (mm)	1524	Door Description	2 Solid Swing Doors	Temperature Holding	0.5 : 3.3°C
External Depth (mm)	631	Exterior Construction	Stainless Steel front and countertop. Matching Aluminium sides & rear.	Refrigerant	R290
External Height (mm)	881	Interior Construction	Stainless Steel	Voltage / Frequency / Phase	220-240V/50-60Hz/1
Exclusions	Depth does not include 35 mm for front + 35 mm for back door handles. Height does not include 7 mm for leg levelers.	Air Intake Position	Front	Amps	1.3
Gross Volume (Litres)	550	Ventilation Position	Front	Wattage	299
Supplied Shelves	6	Clearance Required	Zero back and sides	Defrost Type	Auto
Shelf Size (L x D mm)	551 x 458	Cord Length (Meters)	3.04		
Internal Net Height (mm)	730	Internal Lighting	LED		
Unpackaged Weight (kg)	182	Standard w/ Locks	standard		
Packaged Weight (kg)	193				
Packaged Dimensions (W x D x H mm)	1690 x 801 x 1067				
Supplied with	Product supplied with Levelling Screws. Optional castors sold seperately.				



Specifications subject to change without notice.
Chart dimensions rounded up to the next whole millimeter (inches rounded up to the 1/8")

UK & Ireland

0800 783 2049

EMEA

+41 61 563 07 05

Australia

+61 2 9619 9999

TFIUK@truemfg.com

TrueCHCustomerService@truemfg.com

TrueRefAus@truemfg.com



The technical drawings illustrate the R-22 walk-in freezer's specifications:

- Front View:** Shows a unit with a total width of 60" [1524] and a height of 34 11/16" [881]. The door opening is 20 9/32" [515] wide by 28 5/16" [719] high. A power cord exit is located at the bottom right.
- Side View:** Shows the unit's depth of 30" [762]. It includes details for floor access (ø 2 1/4" [57]), drain access (ø 1" [25]), and condensing unit access (ø 1" [25]).
- Top View:** Provides a plan view of the unit's footprint, showing internal dimensions and radii (R22 31/32" [583]).