

TBR60-RISZ1-L-S-GG-2

 Bar Refrigerator, Stainless Steel Ext, 2 Glass Swing Doors



Dimensions		Build		Technical	
External Width (mm)	1524	Door Description	2 Full Glass Swing Doors	Temperature Holding	0.5 : 3.3°C
External Depth (mm)	631	Exterior Construction	Stainless Steel front and countertop. Matching Aluminium sides & rear.	Refrigerant	R290
External Height (mm)	881			Voltage / Frequency / Phase	220-240V/50-60Hz/1
Exclusions	Depth does not include 35 mm for door handle. Height does not include 7 mm for leg levelers.	Interior Construction	Stainless Steel	Amps	1.3
Gross Volume (Litres)	550	Air Intake Position	Front	Wattage	299
Supplied Shelves	6	Ventilation Position	Front	Defrost Type	Auto
Shelf Size (L x D mm)	551 x 458	Clearance Required	Zero back and sides		
Internal Net Height (mm)	730	Cord Length (Meters)	3.04		
Unpackaged Weight (kg)	169	Internal Lighting	TruLumina®		
Packaged Weight (kg)	180	Standard w/ Locks	standard		
Packaged Dimensions (W x D x H mm)	1690 x 724 x 1067				
Supplied with	Product supplied with Levelling Screws. Optional castors sold seperately.				



Specifications subject to change without notice.
Chart dimensions rounded up to the next whole millimeter (inches rounded up to the 1/8")

UK & Ireland
EMEA
Australia

0800 783 2049
+41 61 563 07 05
+61 2 9619 9999

TFIUK@truemfg.com
TrueCHCustomerService@truemfg.com
TrueRefAus@truemfg.com



TBR60-RISZ1-L-S-GG-2

 Bar Refrigerator, Stainless Steel Ext, 2 Glass Swing Doors

